



Common Council Meeting Agenda

Thursday, May 07, 2026 at 6:30 PM

Columbus City Hall – 105 N. Dickason Boulevard

Roll Call

Pledge of Allegiance

Notice of Open Meeting

Approval of Agenda

Public Comment *(Public comments will be limited to three (3) minutes per speaker. Speakers must begin by stating their name and address for the record. To ensure that all individuals have an opportunity to be heard, the presiding officer may enforce the time limit and may call speakers to conclude their remarks when their time has expired.)*

New Business

1. Consider and take action regarding the purchase of a 2026 HV507 SFA International Front Plow Truck and Wing with spreader from Lakeside International in the amount of \$259,524.71.

Report of City Officers – City Administrator, Mayor

Adjourn

*A quorum of city committees and/or commissions may be present at this meeting. No action will be taken or considered by those committees and/or commissions.



Agenda Item Report

Meeting Type: Committee of the Whole/Common Council Meeting

Meeting Date: May 5, 2026

Item Title: Purchase Request of an International Front Plow and Wing with Spreader from Lakeside International for Public Works

Submitted By: Randall Myrum, Director of Public Works and Utilities

Detailed Description of Subject Matter: The Capital Improvement Plan for 2026 included the purchase of a new plow truck for the Department of Public Works. Director Myrum was recently contacted by Lakeside International Trucks and informed that the previous director of Columbus DPW had selected a truck from their organization and that said truck was ready for delivery.

Although the proposed plow truck, a 2026 HV 507 SFA single axle front plow and wing with spreader, is considered a good acquisition and asset for the DPW, Director Myrum cannot confirm if the proper procurement procedures were followed and at least three quotes were obtained for consideration.

List all Supporting Documentation Attached:

Truck model specification packet

Action Requested of Council:

Director Myrum seeks the council's permission to complete the proposed purchase.

Prepared For:
City of Columbus
Duane Millard
123 Main St
Columbus, OH 00000-
(920)444 - 1212
Reference ID: 14439X

Presented By:
LAKESIDE INTERNATIONAL TRUCKS
Hank Wieland
7243 MANUFACTURERS DRIVE
MADISON WI 53704 -
(608)246-5860



Model Profile
2026 HV507 SFA (HV507)

AXLE CONFIG: 4X2
APPLICATION: Front Plow and Wing with Spreader
MISSION: Requested GVWR: 43000. Calc. GVWR: 43000. Calc. GCWR: 80000
Calc. Start / Grade Ability: 28.18% / 3.12% @ 55 MPH
Calc. Geared Speed: 73.5 MPH
DIMENSION: Wheelbase: 161.00, CA: 86.00, Axle to Frame: 79.00
ENGINE, DIESEL: {Cummins L9 350} EPA 2024, 350HP @ 2200 RPM, 1050 lb-ft Torque @ 1200 RPM, 2200 RPM Governed Speed, 350 Peak HP (Max)
TRANSMISSION, AUTOMATIC: {Allison 3000 RDS} 6th Generation Controls, Close Ratio, 6-Speed with Double Overdrive, with PTO Provision, Less Retarder, Includes Oil Level Sensor, with 80,000-lb GVW and GCW Max, On/Off Highway
CLUTCH: Omit Item (Clutch & Control)
AXLE, FRONT NON-DRIVING: {Meritor MFS-20-133A} Wide Track, I-Beam Type, 20,000-lb Capacity
AXLE, REAR, SINGLE: {Meritor RS-23-160} Single Reduction, 23,000-lb Capacity, Driver Controlled Locking Differential, 200 Wheel Ends Gear Ratio: 5.63
CAB: Conventional, Day Cab
TIRE, FRONT: (2) 315/80R22.5 Load Range L HAU 3 WT (CONTINENTAL), 480 rev/mile, 68 MPH, All-Position

TIRE, REAR: (4) 11R22.5 Load Range H HDR2+ (CONTINENTAL), 491 rev/mile, 75 MPH, Drive

SUSPENSION, REAR, AIR, SINGLE: {Hendrickson PRIMAAX EX} 23,000-lb Capacity, 9.0" Ride Height, with Shock Absorbers

PAINT: Cab schematic 100WK
Location 1: 0311, Omaha Orange (Std)
Chassis schematic N/A

Description

Base Chassis, Model HV507 SFA with 161.00 Wheelbase, 86.00 CA, and 79.00 Axle to Frame.

AXLE CONFIGURATION

AXLE CONFIGURATION 4x2

Notes

: Pricing may change if axle configuration is changed.

ENGINE

ENGINE, DIESEL {Cummins L9 350} EPA 2024, 350HP @ 2200 RPM, 1050 lb-ft Torque @ 1200 RPM, 2200 RPM Governed Speed, 350 Peak HP (Max)

EMISSION, CALENDAR YEAR {Cummins L9} EPA, OBD and GHG Certified for Calendar Year 2026

CARB EMISSION WARR COMPLIANCE Does Not Comply with CARB Emission Warranty

CARB IDLE COMPLIANCE Does Not Comply with California Clean Air Idle Regulations

EPA IDLE COMPLIANCE Low NOx Idle Engine, Complies with EPA Clean Air Regulations; Includes "Certified Clean Idle" Decal on Door

VEHICLE REGISTRATION IDENTITY ID for Non-CARB Omnibus and/or Non-ACT Adopting State or Exempt Vehicle. Not for use on vehicles registering in CA. Contains non-mitigated legacy engine & cannot be registered in CA unless exempt. You may be held liable under state law for failure to properly register vehicle.

Notes

: CANNOT BE REGISTERED IN CA. For vehicles that will be registered in States other than CA.

RADIATOR Aluminum, Cross Flow, Front to Back System, 1228 SqIn, with 1167 SqIn Charge Air Cooler, Includes In-Tank Oil Cooler

Includes

: DEAERATION SYSTEM with Surge Tank

: HOSE CLAMPS, RADIATOR HOSES Gates Shrink Band Type; Thermoplastic Coolant Hose Clamps

: RADIATOR HOSES Premium, Rubber

FAN DRIVE {Horton Drivemaster} Two-Speed Type, Direct Drive, with Residual Torque Device for Disengaged Fan Speed

Includes

: FAN Nylon

AIR CLEANER Single Element, with Integral Snow Valve and In-Cab Control

ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection

BLOCK HEATER, ENGINE 120V/1000W, for Cummins ISB/B6.7/ISL/L9 Engines

Includes

: BLOCK HEATER SOCKET Receptacle Type; Mounted below Drivers Door

Description

ENGINE CONTROL, REMOTE MOUNTED No Provision for Remote Mounted Engine Control

PTO EFFECTS, ENGINE FRONT Less PTO Unit, Includes Adapter Plate on Engine Front Mounted

THROTTLE, HAND CONTROL Engine Speed Control; Electronic, Stationary, Variable Speed; Mounted on Steering Wheel

TRANSMISSION

TRANSMISSION, AUTOMATIC {Allison 3000 RDS} 6th Generation Controls, Close Ratio, 6-Speed with Double Overdrive, with PTO Provision, Less Retarder, Includes Oil Level Sensor, with 80,000-lb GVW and GCW Max, On/Off Highway

TRANSMISSION TCM LOCATION Located Inside Cab

ALLISON SPARE INPUT/OUTPUT for Rugged Duty Series (RDS) and Regional Haul Series (RHS), General Purpose Trucks, Construction, Package Number 223

NEUTRAL AT STOP Allison Transmission Shifts to Neutral When Service Brake is Depressed and Vehicle is at Stop; Remains in Neutral Until Service Brake is Released

PTO LOCATION Dual, Customer Intends to Install PTO at Left and/or Right Side of Transmission

SHIFT CONTROL PARAMETERS {Allison} 3000 or 4000 Series Transmissions, S1 Performance in Primary and Fixed Programming in Secondary

TRANSMISSION DIPSTICK Relocated to Right Side of Transmission

TRANSMISSION OIL Synthetic; 29 thru 42 Pints

TRANSMISSION SHIFT CONTROL Column Mounted Stalk Shifter, Not for Use with Allison 1000 & 2000 Series Transmission

CLUTCH

CLUTCH Omit Item (Clutch & Control)

REAR AXLES, SUSPENSIONS

AXLE, REAR, SINGLE {Meritor RS-23-160} Single Reduction, 23,000-lb Capacity, Driver Controlled Locking Differential, 200 Wheel Ends . Gear Ratio: 5.63

SUSPENSION, REAR, AIR, SINGLE {Hendrickson PRIMAAX EX} 23,000-lb Capacity, 9.0" Ride Height, with Shock Absorbers

SUSPENSION AIR CONTROL VALVE Pressure Release Control In Cab

FRONT AXLES

AXLE, FRONT NON-DRIVING {Meritor MFS-20-133A} Wide Track, I-Beam Type, 20,000-lb Capacity

FRONT SUSPENSIONS

Description

SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 20,000-lb Capacity, with Shock Absorbers

CABS, COWLS, BODIES

CAB Conventional, Day Cab

ACCESS, CAB Bright Aluminum, Driver & Passenger Sides, Two Steps per Door, for use with Day Cab or Extended Cab

AIR CONDITIONER with Integral Heater and Defroster

ARM REST, RIGHT, DRIVER SEAT

AUTOMATIC CLIMATE CONTROL Automatically Maintains Cabin Comfort Based on Selected Temperature

CAB INTERIOR TRIM Diamond, for Day Cab

Includes

: CONSOLE, OVERHEAD Molded Plastic with Dual Storage Pockets, Retainer Nets and CB Radio Pocket; Located Above Driver and Passenger

: DOME LIGHT, CAB Door Activated and Push On-Off at Light Lens, Timed Theater Dimming, Reading Lights; Integral to Overhead Console, Center Mounted

: SUN VISOR (3) Padded Vinyl; 2 Moveable (Front-to-Side) Primary Visors, Driver Side with Vanity Mirror and Toll Ticket Strap, plus 1 Auxiliary Visor (Front Only), Driver Side

CAB REAR SUSPENSION Air Bag Type

FLOOR, COATING LINE-X, Applied to Interior Cab Floor

FRESH AIR FILTER Attached to Air Intake Cover on Cowl Tray in Front of Windshield Under Hood

GAUGE CLUSTER Premium Level; English with English Electronic Speedometer

Includes

: GAUGE CLUSTER DISPLAY: Base Level (3" Monochromatic Display), Premium Level (5" LCD Color Display); Odometer, Voltmeter, Diagnostic Messages, Gear Indicator, Trip Odometer, Total Engine Hours, Trip Hours, MPG, Distance to Empty/Refill for

: GAUGE CLUSTER Speedometer, Tachometer, Engine Coolant Temp, Fuel Gauge, DEF Gauge, Oil Pressure Gauge, Primary and Secondary Air Pressure

: WARNING SYSTEM Low Fuel, Low DEF, Low Oil Pressure, High Engine Coolant Temp, Low Battery Voltage (Visual and Audible), Low Air Pressure (Primary and Secondary)

GAUGE, AIR CLEANER RESTRICTION {Filter-Minder} Mounted in Instrument Panel

GAUGE, OIL TEMP, AUTO TRANS for Allison Transmission

GRAB HANDLE, EXTERIOR (2) Chrome, for Cab Entry, (1) Towel Bar Type, with Anti-Slip Rubber Inserts Mounted Left Side at B-Pillar, (1) Towel Bar Type Mounted Right Side on Vertical Exhaust

GRAB HANDLE, CAB INTERIOR (2) Safety Yellow

HEATER SHUT-OFF VALVES (1) Ball Valve Type, Supply Line

Description

INSTRUMENT PANEL Wing Panel

IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster

MIRRORS (2) Aero Pedestal, Power Adjust, Heated, Turn Signals, Black Heads and Arms, 6.5" x 14" Flat Glass, Includes 6.5" x 6" Convex Mirrors, for 102" Load Width

Notes

: Mirror Dimensions are Rounded to the Nearest 0.5"

MIRROR, CONVEX, LOOK DOWN Right Side, Black, 6" x 10.5"

MIRROR, CONVEX, HOOD MOUNTED {Lang Mekra} (2) Right and Left Sides, Black, Heated, 7.5" Sq.

MONITOR, TIRE PRESSURE Omit

SEAT, DRIVER {National 2000 195} Air Suspension, High Back with Integral Head Rest, Cloth, Isolator, 8" Adjuster, 1 Chamber Lumbar, 2 Position Front Cushion Adjust, 6-23 Degree Back Angle Adjust, Dual Shocks

SEAT, PASSENGER {Seats, Inc.} Non Suspension, High Back, Fixed Back, Integral Headrest, Cloth, for use with Batteries in Cab

SUNSHADE, EXTERIOR Bright Finish, with Integral Clearance/Marker Lights

WINDOW, POWER (2) and Power Door Locks, Left and Right Doors, Includes Express Down Feature

WINDSHIELD Heated, Single Piece

WINDSHIELD WASHER RESERVOIR Mounted Under Cab with Remote Fill Mounted Behind Cab Drivers Side

FRAMES

FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.866" x 3.622" x 0.437" (276.0mm x 92.0mm x 11.1mm); 456.0" (11582mm) Maximum OAL

BRACKET, CAB MOUNT Heavy Duty

BUMPER, FRONT Swept Back, Steel, Heavy Duty

FRAME EXTENSION, FRONT Integral; 20" In Front of Grille

TOW HOOK, FRONT (2) Frame Mounted

WHEELBASE RANGE 146" (370cm) Through and Including 195" (495cm)

BRAKES

BRAKE SYSTEM, AIR Dual System for Straight Truck Applications

Includes

: BRAKE LINES Color and Size Coded Nylon

: DRAIN VALVE Twist-Type

: GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster

Description

: PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel

: PARKING BRAKE VALVE For Truck

: QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4

: SPRING BRAKE MODULATOR VALVE R-7 for 4x2, SR-7 with relay valve for 6x4/8x6

AIR BRAKE ABS {Bendix AntiLock Brake System} 4-Channel (4 Sensor/4 Modulator) Full Vehicle Wheel Control System, with Automatic Traction Control

BRAKE, PARKING Manual Push-Pull Pneumatic Parking Brake

BRAKES, FRONT {Meritor 16.5X6 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 6", 23,000-lb Capacity

BRAKE CHAMBERS, FRONT AXLE {Bendix} 24 SqIn

SLACK ADJUSTERS, FRONT {Haldex} Automatic

DUST SHIELDS, FRONT BRAKE for Air Cam Brakes

BRAKES, REAR {Meritor 16.5X7 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 7", 23,000-lb Capacity per Axle

BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 SqIn Spring Brake

SLACK ADJUSTERS, REAR {Haldex} Automatic

DUST SHIELDS, REAR BRAKE for Air Cam Brakes

AIR COMPRESSOR {Cummins} 18.7 CFM

AIR DRYER {Wabco System Saver 1200} with Heater

AIR DRYER LOCATION Mounted Inside Left Rail, Back of Cab

AIR TANK LOCATION (2) : One Mounted Under Each Rail, Front of Rear Suspension, Parallel to Rail

DRAIN VALVE {Berg} with Pull Chain, for Air Tank

STEERING

STEERING GEAR (2) {Sheppard M100/M80} Dual Power

STEERING COLUMN Tilting and Telescoping

STEERING WHEEL 4-Spoke; 18" Dia., Black

DRIVELINES

DRIVELINE SYSTEM {Dana Spicer} SPL140, for 4x2/6x2

EXHAUST SYSTEMS

EXHAUST SYSTEM Horizontal Aftertreatment System, Frame Mounted Right Side Under Cab, for Single Vertical Tail Pipe, Frame Mounted Right Side Back of Cab

Description

AFTERTREATMENT COVER Polished Aluminum

ENGINE EXHAUST BRAKE for Cummins ISB/B6.7/ISL/L9 Engine with Variable Vane Turbo Charger

EXHAUST HEIGHT 8' 10"

MUFFLER/TAIL PIPE GUARD (1) Bright Stainless Steel

TAIL PIPE (1) Turnback Type, Bright

ELECTRICAL SYSTEMS

ELECTRICAL SYSTEM 12-Volt, Standard Equipment

Includes

: DATA LINK CONNECTOR For Vehicle Programming and Diagnostics In Cab

: HAZARD SWITCH Push On/Push Off, Located on Instrument Panel to Right of Steering Wheel

: HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever

: PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light

: STARTER SWITCH Electric, Key Operated

: STOP, TURN, TAIL & B/U LIGHTS Dual, Rear, Combination with Reflector

: TURN SIGNAL SWITCH Self-Cancelling for Trucks, Manual Cancelling for Tractors, with Lane Change Feature

: WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever

: WINDSHIELD WIPERS Single Motor, Electric, Cowl Mounted

: WIRING, CHASSIS Color Coded and Continuously Numbered

ACCESSORY WIRING, SPECIAL for Road Speed Wire Coiled Under Instrument Panel for Customer Use

ALARM, PARKING BRAKE Electric Horn Sounds in Repetitive Manner When Vehicle Park Brake is "NOT" Set, with Ignition "OFF" and any Door Opened

ALTERNATOR {Leece-Neville AVI160P2013} Brush Type, 12 Volt, 160 Amp Capacity, Pad Mount, with Remote Sense

ANTENNA Shark Fin, Roof Mounted

AUXILIARY HARNESS 3.0' for Auxiliary Front Head Lights and Turn Signals for Front Plow Applications

BATTERY BOX Steel, 2-3 Battery Capacity, Mounted Inside the Cab, Under Passenger Seat

BATTERY DISCONNECT SWITCH 300 Amp, Disconnects Charging Circuits, Locks with Padlock, Cab Mounted

BATTERY SYSTEM {Fleetrice AGM-GP31} Maintenance-Free, (3) AGM 12-Volt 2475CCA Total, Top Threaded Stud

BODY BUILDER WIRING Back of Day Cab at Left Frame or Under Sleeper, Extended or Crew Cab at Left Frame; Includes Sealed Connectors for Tail/Amber Turn/Marker/ Backup/Accessory Power/Ground and Sealed Connector for Stop/Turn

Description

2-WAY RADIO Wiring Effects; Wiring with 20 Amp Fuse Protection, Includes Ignition Wire with 5 Amp Fuse, Wire Ends Heat Shrink and Routed to Center of Header Console in Cab

CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses

CLEARANCE/MARKER LIGHTS (5) {Truck Lite} Amber LED Lights, Flush Mounted on Cab or Sunshade

CONNECTOR, DASH, CENTER PANEL Cab Wiring for TMC RP1226 Vehicle Accessory Connector; Includes 14-pin Connector with Switched Power, Battery Power, Ignition Power, Ground & Body 250K Datalink, Connector Located Behind Instrument Panel Center Console

HEADLIGHTS Halogen

HEADLIGHTS ON W/WIPERS Headlights Will Automatically Turn On if Windshield Wipers are Turned On

HORN, AIR Single Trumpet, Black, with Lanyard Pull Cord

HORN, ELECTRIC Disc Style

INDICATOR, LOW COOLANT LEVEL with Audible Alarm

JUMP START STUD (2) 12V, Remote Mounted

POWER SOURCE, ADDITIONAL Auxiliary Power Outlet (APO) with USB-A Port and USB-C Port, Located in the Instrument Panel

RADIO AM/FM/WB/Clock/Bluetooth/USB Input/Auxiliary Input

RADIO, STEERING WHEEL CONTROLS Mounted in Steering Wheel, Radio Function Control Switch, Includes Volume Up/Down, Mute, Forward/Back and Bluetooth Answer/Disconnect

SPEAKERS (2) 6.5" Dual Cone Mounted in Both Doors, (2) 5.25" Dual Cone Mounted in Both B-Pillars

STARTING MOTOR {Mitsubishi Electric Automotive America 105P} 12-Volt, with Soft-Start

STOP, TURN, TAIL & B/U LIGHTS {Weldon} Multi-Function LED Lamp, Mounted Outside Rails, Includes LED License Plate Light

SWITCH, BODY CIRCUITS, MID with Remote Power Module Mounted in Cab Behind Driver Seat, Up to 6 Outputs & 6 Inputs, Max 20 amp per Channel, Max 80 amp Total, Includes 1 Switch Pack with Momentary Switches

TEST EXTERIOR LIGHTS Pre-Trip Inspection will Cycle all Exterior Lamps Except Back-up Lights

TURN SIGNALS, FRONT Includes LED Side Turn Lights Mounted on Fender

USB PORT One USB-A Port and One USB-C Port, Located in Instrument Panel

WINDSHIELD WIPER SPD CONTROL Force Wipers to Slowest Intermittent Speed When Park Brake Set and Wipers Left on for a Predetermined Time

VIDEO CAMERA WIRING Pre-Wire Only, for DriveCam Driver Monitoring System; Battery/Ignition Power and Vehicle Data Provided for Installer, Located in Center Panel, for Use with DC3P Camera

Description
FRONT END

FRONT END Tilting, Fiberglass, with Three Piece Construction, for WorkStar/HV
 FENDER EXTENSIONS Rubber
 GRILLE Stationary, Chrome
 HOOD, HATCH (01) for Servicing
 INSULATION, SPLASH PANELS for Sound Abatement
 INSULATION, UNDER HOOD for Sound Abatement
 LOGOS EXTERIOR Model Badges
 LOGOS EXTERIOR, ENGINE Badges

SPEEDOMETER, TOOLS, MISC

CHASSIS COATING Corrosion Resistant E-Coat Primer Coating for Single Frame Rails
 CONNECTED PLATFORM Includes Connectivity Module and Five Year Data Plan
 CUSTOMER IDENTITY for Sourcewell
 FIRE EXTINGUISHER 5 lb Class A B C
 FIRE EXTINGUISHER BRACKET Mounted Left Side Driver Seat
 KEYS - ALL ALIKE, ADDITIONAL 2 Keys
 KEYS - ALL ALIKE, ID I-1624 Compatible with Z-250
 LABEL, DEF "DEF ONLY"
 PAINT SCHEMATIC, PT-1 Single Color, Design 100

Includes

: PAINT SCHEMATIC ID LETTERS "WK"
 PAINT TYPE Base Coat/Clear Coat, 1-2 Tone
 PROMOTIONAL PACKAGE Government Silver Package
 SAFETY TRIANGLES

FUEL TANKS

FUEL TANK Top Draw, Polished Aluminum, D-Style, 19" Tank Depth, 70 US Gal (265L), Mounted Left Side, Under Cab
 DEF TANK 7 US Gal (26L) Capacity, Frame Mounted Outside Left Rail, Under Cab
 FUEL TANK STRAPS Bright Finish Stainless Steel

Description

FUEL/WATER SEPARATOR {Racor 400 Series} 12 VDC Electric Heater, Includes Pre-Heater, with Primer Pump, Includes Water-in-Fuel Sensor, Mounted on Engine

WHEELS, TIRES - FRONT

WHEELS, FRONT {Accuride 41730} DISC; 22.5x9.00 Rims, Standard Polish Aluminum, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs

(2) TIRE, FRONT 315/80R22.5 Load Range L HAU 3 WT (CONTINENTAL), 480 rev/mile, 68 MPH, All-Position

WHEELS, TIRES - REAR

WHEELS, REAR {Accuride 43644} DUAL DISC; 22.5x8.25 Rims, Standard Polish Aluminum, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs

(4) TIRE, REAR 11R22.5 Load Range H HDR2+ (CONTINENTAL), 491 rev/mile, 75 MPH, Drive

BODY INTEGRATION

BDY INTG, PTO ACCOMMODATION for (3) Latched Rocker Switches, (1) PTO Switch, (2) Generic Switches to Control (3) 30 amp relays, with Programmable Interlocks, for Body Builder Hook up in the Engine Compartment Left Side, Recommended for Automatic Transmissions

Cab schematic 100WK

Location 1: 0311, Omaha Orange (Std)

Chassis schematic N/A

Services Section:

WARRANTY

WARRANTY Standard for HV507/HV509, HV50B, HV607/HV609 Models, Effective with Vehicles Built July 1, 2017 or Later, CTS-2025A

Caspers Package

Casper's Patrol Equipment Package

Financial Summary
2026 HV507 SFA (HV507)

(US DOLLAR)

Description

Price

Net Sales Price:

\$259,524.71

Please feel free to contact me regarding these specifications should your interests or needs change. I am confident you will be pleased with the quality and service of an International vehicle.

Approved by Seller:

Accepted by Purchaser:

Official Title and Date

City of Columbus, WI

Firm or Business Name

3/27/2026

Authorized Signature

Authorized Signature and Date

This proposal is not binding upon the seller without Seller's Authorized Signature

Signature valid following final inspection of unit.

Director of Public Works

Official Title and Date

If you haven't added a planned maintenance service contract to your proposal yet, please get in touch with your local dealer, International or IC Bus Sales Representative to learn more about the benefits when ordering together with the vehicle.

International® Financial offers loans, a full line up of lease options, and can establish a line of credit for use towards the purchase of International and IC Bus vehicles. Ask your dealer, International® or IC Bus® Sales Representative about completing an International Financial credit application and any promotional offers that may be available. International Financial services are provided by Navistar Financial Corporation.

The TOPS FET Calculation is an estimate for reference purposes only. The seller is responsible for calculating and reporting/paying appropriate FET to the IRS.

The limited warranties applicable to the vehicles described here in are International Motors, LLC* standard printed warranties which are incorporated herein by reference and to which you have been provided a copy and hereby agree to their terms and conditions.

International Motors, LLC d/b/a International Motors USA LLC in Illinois and Ohio.