

BOARD OF PUBLIC WORKS

City of Kaukauna
Council Chambers
Municipal Services Building
144 W. Second Street, Kaukauna



Monday, July 31, 2023 at 6:00 PM

AGENDA

In-Person

1. Correspondence.
2. Discussion Topics.
 - a. [Authorization to seek bids for Project 13-23: Company Woods Pond.](#)
 - b. Municipal Pool Project Update - Mini Golf Discussion.
 - c. Public Works Update.
3. Adjourn.

NOTICES

Notice is hereby given that a majority of the City Council will be present at the meeting of the Board of Public Works meeting scheduled for Monday, July 31, 2023 at 6:00 P.M. to gather information about a subject over which they have decision making responsibility.

IF REQUESTED THREE (3) DAYS PRIOR TO THE MEETING, A SIGN LANGUAGE INTERPRETER WILL BE MADE AVAILABLE AT NO CHARGE.



City of Kaukauna**Board of Public Works****August 1, 2023**

jn/engr dept

Agenda Item #2a**Authorization to seek bids for Project 13-23 Company Woods Pond****Background**

The Engineering Department is requesting authorization to seek bids for the Company Woods Pond retrofit project. The pond modifications are part of the approved Total Maximum Daily Loading (TMDL) action plan and budgeted work plan submitted to DNR for the City. The project will take an existing pond that does not meet current standards for removal of suspended solids or phosphorus and will increase the depth and surface area to allow for enhanced treatment of the stormwater before it enters the company woods stream and the Lower Fox River. A second phase of this project will create a wetland safety shelf and mesic prairies, as well as planting trees around the pond area. The additions will provide habitat and a low maintenance natural area within the 1000 Islands Conservancy Zone. An urban non-point source grant for the retrofit project was received from WI DNR and will reimburse up to 50% of the project cost. A plan set is attached to this memo.

Recommended Action



Motion to authorize the Engineering Department to seek bids for Project 13-23, Company Woods Pond.

COMPANY WOODS POND

CITY OF KAUKAUNA

OUTAGAMIE COUNTY, WISCONSIN

MCM # K0006-092200453



CONTACT INFORMATION

UTILITIES
WE ENERGIES
CODY BECKMAN (GAS)
KENNETH VAN OSS (ELECTRIC)
800 SOUTH LYNDALE DRIVE P.O. BOX 1699
APPLETON, WI 54912
(920) 380-3422 (GAS)
(920) 380-3318 (ELECTRIC)
cody.beckman@we-energies.com
kenneth.van-oss@we-energies.com

AT&T
ERIC ADAIR
205 S. JEFFERSON ST.
GREEN BAY, WI 54301
(920) 433-4155
az9216@att.com

TIME WARNER CABLE
VINCE ALBIN
3520 DESTINATION DRIVE
APPLETON, WI 54915
(920) 378-0444
vince.albin@twcable.com

KAUKAUNA UTILITIES, ELECTRIC
ERIC MILLER
777 ISLAND STREET
P.O. BOX 1777
KAUKAUNA, WI 54130-7077
(920) 462-0214
emiller@wppsys.org

KAUKAUNA UTILITIES, WATER
KEVIN OBIALA
777 ISLAND STREET
P.O. BOX 1777
KAUKAUNA, WI 54130-7077
(920) 462-0233
kobiala@ku-wi.org

OWNER CONTACT
CITY OF KAUKAUNA
JOHN NEUMEIER, PROJECT ENGINEER
201 W. SECOND STREET
P.O. BOX 890
KAUKAUNA, WI 54130-0890
PHONE (920) 766-6305

DESIGN CONTACT
McMAHON
ANDREW SCHMIDT
1445 McMAHON DRIVE
NEENAH, WI 54956
(920) 751-4200
aschmidt@mcmgrp.com

DNR
DEPARTMENT OF NATURAL RESOURCES
CRYSTAL VON HOLDT
2984 SHAWANO AVENUE
GREEN BAY, WI 54313-6727
(920) 662-5466
crystal.vonholdt@wi.gov



Dial 811 or (800) 242-8511
www.DiggersHotline.com

McMAHON

ENGINEERS ARCHITECTS

McMAHON ASSOCIATES, INC.
1445 McMAHON DRIVE NEENAH, WI 54956
Mailing: P.O.BOX 1025 NEENAH, WI 54957-1025
PH 920.751.4200 FX 920.751.4284 MCMGRP.COM

SHEET INDEX

- 01 - ABBREVIATIONS SYMBOLS & NOTES
- 02 - SURVEY CONTROL
- 03 - EXISTING SITE PLAN
- 04 - PROPOSED POND PLAN
- 05 - LANDSCAPE PLAN
- 06 - MISCELLANEOUS DETAIL
- 07 - MISCELLANEOUS DETAIL

g:\schmidt\w:\PROJECTS\K0006\092200453\CADD\Civil3D\Plan Sheets\00 Title-Notes-Details.dwg, 01 abbreviations symbols & notes, Plot Date: 7/20/2023 11:18 AM, xrefs:none

STANDARD ABBREVIATIONS

AGG	ACRE	LT	LEFT
AH	AGGREGATE	LVC	LENGTH OF VERTICAL CURVE
ASPH	AHEAD	MAINT	MAINTENANCE
AVG	ASPHALT PAVEMENT	MAT'L	MATERIAL
B-B	AVERAGE	MAX	MAXIMUM
BEG	BACK TO BACK	MIN	MINIMUM
BIT	BEGIN	MH	MANHOLE
BK	BITUMINOUS	MP	MILE POST
B/L	BACK	NB	NORTHBOUND
BLDG	BASE LINE	NO	NUMBER
BM	BUILDING	NOR	NORMAL
BOC	BENCH MARK	OD	OUTSIDE DIAMETER
BRG	BACK OF CURB	OBLIT	OBLITERATE
C-C	BEARING	PAV'T	PAVEMENT
CY	CENTER TO CENTER	PC	POINT OF CURVATURE
C&G	CUBIC YARD	PCC	PORTLAND CEMENT CONCRETE OR
CB	CURB AND GUTTER		POINT OF COMPOUND CURVATURE
CE	CATCH BASIN	PE	PRIVATE ENTRANCE
CHD	COMMERCIAL ENTRANCE	PED	PEDESTAL
C/L	CHORD	PGL	PROFILE GRADE LINE
CL	CENTER LINE	PI	POINT OF INTERSECTION
CMF	CLASS (FOR CONC PIPE)	P/L	PROPERTY LINE
CO	CORRUGATED METAL PIPE	PLE	PERMANENT LIMITED EASEMENT
CONC	CLEAN OUT	PP	POWER POLE
CORR	CONCRETE	PRC	POINT OF REVERSE CURVATURE
CP	CORRUGATED	PROP	PROPOSED
CR	CONTROL POINT	PSD	PASSING SIGHT DISTANCE
CS	CRUSHED	PSI	POUNDS PER SQUARE INCH
CSW	CURB STOP	PT	POINT OF TANGENCY
CTH	CONCRETE SIDEWALK	PVC	POLYVINYL CHLORIDE OR
CULV	COUNTY TRUNK HIGHWAY		POINT OF VERTICAL CURVATURE
D	CULVERT	PVI	POINT OF VERTICAL INTERSECTION
DI	DEPTH OR DELTA	PVT	POINT OF VERTICAL TANGENCY
DIA	DUCTILE IRON	R	RADIUS
DIS	DIAMETER	RCP	REINFORCED CONCRETE PIPE
EA	DISCHARGE	RD	ROAD
EB	EACH	REBAR	REINFORCEMENT ROD
EBS	EASTBOUND	REM	REMOVE
EG	EXCAVATION BELOW SUBGRADE	RECON	RECONSTRUCT
ELEV	EDGE OF GRAVEL	REQ'D	REQUIRED
ELEC	ELEVATION	R/L	REFERENCE LINE
EMB	ELECTRIC	RP	RADIUS POINT
EMAT	EMBANKMENT	RR	RAILROAD
ENT	EROSION MAT	RT	RIGHT
EOR	ENTRANCE	R/W	RIGHT-OF-WAY
EP	END OF RADIUS	SB	SOUTHBOUND
EXC	EDGE OF PAVEMENT	SE	SUPERELEVATION
EX	EXCAVATION	SF	SQUARE FEET
EW	EXISTING	SI	SLOPE INTERCEPT
F-F	ENDWALL	STH	STATE TRUNK HIGHWAY
FDN	FACE TO FACE	SY	SQUARE YARD
FE	FOUNDATION	SALV	SALVAGED
FERT	FIELD ENTRANCE	SAN	SANITARY
FG	FERTILIZER	SEC	SECTION
F/L	FINISHED GRADE	SHLDR	SHOULDER
FT	FLOW LINE	S/L	SURVEY LINE
FTG	FOOT	SQ	SQUARE
GRAV	FOOTING	STA	STATION
GN	GRAVEL	STD	STANDARD
GV	GRID NORTH	STO	STORM
HDPE	GAS VALVE	SW	SIDEWALK
HE	HIGH DENSITY POLYETHYLENE	TC	TOP OF CURB
HMA	HIGHWAY EASEMENT	TEL	TELEPHONE
HP	HOT MIX ASPHALT	TEMP	TEMPORARY
HT	HIGH POINT	TLE	TEMPORARY LIMITED EASEMENT
HYD	HEIGHT	TV	TELEVISION
ID	HYDRANT	TYP	TYPICAL
IN	INSIDE DIAMETER	UG	UNDERGROUND
INL	INCH	USH	U.S. HIGHWAY
INV	INLET	VAR	VARIES
IP	INVERT	VC	VERTICAL CURVE
JCT	IRON PIPE	VERT	VERTICAL
LB	JUNCTION	WB	WESTBOUND
LF	POUND	WM	WATER MAIN
LP	LINEAR FOOT	WV	WATER VALVE
	LIGHT POLE		

GENERAL NOTES

- THE UTILITIES SHOWN IN PLAN AND PROFILE ARE INDICATED IN ACCORDANCE WITH AVAILABLE RECORDS. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING EXACT LOCATIONS AND ELEVATIONS OF ALL UTILITIES, INCLUDING ANY PRIVATE UTILITIES, FROM THE OWNERS OF THE RESPECTIVE UTILITIES. ALL UTILITIES SHALL BE NOTIFIED 72 HRS. PRIOR TO EXCAVATION.
- PRIOR TO CONSTRUCTION, THE CONTRACTOR SHALL VERIFY PROPOSED SITE GRADES BY FIELD CHECKING TWO (2) BENCHMARKS AND A MINIMUM OF ONE (1) SITE FEATURE AS SHOWN ON THESE PLANS. THE CONTRACTOR SHALL IMMEDIATELY NOTIFY MCMAHON OF ANY VERTICAL DISCREPANCY.
- EXISTING STREET RIGHT-OF-WAY AND INTERSECTING PROPERTY LINES ARE ESTABLISHED FROM FIELD LOCATED SURVEY MONUMENTATION, PREVIOUS SURVEYS, PLATS AND CURRENT PROPERTY DEEDS.
- NO TREES OR SHRUBS ARE TO BE REMOVED WITHOUT PRIOR APPROVAL FROM THE OWNER.
- A SAWED JOINT IS REQUIRED WHERE NEW HMA PAVEMENT MATCHES EXISTING ASPHALTIC CONCRETE SURFACE.
- ALL CURB RADII SHOWN ON THE PLAN SHEETS ARE TO THE BACK OF CURB UNLESS OTHERWISE NOTED.
- DIMENSIONS ARE TO THE BACK OF CURB UNLESS OTHERWISE NOTED.

STANDARD SYMBOLS (PLAN VIEW ONLY)

	2" IRON PIPE FOUND		TELEPHONE CABLE - BURIED
	1 1/4" REBAR FOUND		ELECTRIC CABLE - BURIED
	1 1/4" x 30" IRON REBAR WEIGHING 4.30 LB/LF SET		UTILITIES - OVERHEAD
	1" (1.315 OD) IRON PIPE FOUND		FIBER OPTIC CABLE - BURIED
	1" IRON PIPE SET		GAS MAIN
	3/4" IRON REBAR FOUND		CABLE TELEVISION - BURIED
	3/4" IRON PIPE FOUND		DITCH LINE
	3/4"x 24" IRON REBAR WEIGHING 1.5 LB/LF SET		STREET C/L OR R/L
	MAG NAIL FOUND		PROPERTY LINE
	MAG NAIL SET		RIGHT-OF-WAY LINE
	MAG SPIKE FOUND		SECTION LINE
	MAG SPIKE SET		EXISTING CONTOURS
	CHISEL CROSS FOUND		PROPOSED CONTOURS
	CHISEL CROSS SET		EXISTING FORCEMAIN SEWER
	COUNTY MONUMENT		EXISTING SANITARY SEWER
	CONCRETE MONUMENT FOUND		PROPOSED SANITARY SEWER
	CONTROL POINT HORIZONTAL		EXISTING WATER MAIN
	VERTICAL BENCHMARK		PROPOSED WATER MAIN
	SOIL BORING or MONITORING WELL		EXISTING STORM SEWER
	POWER POLE		PROPOSED STORM SEWER
	POWER POLE W/GUY WIRE		EXISTING CURB & GUTTER
	TELEPHONE OR TELEVISION PEDESTAL		PROPOSED CURB & GUTTER
	MAILBOX		PROPOSED REJECT CURB & GUTTER
	SIGN		EXISTING CULVERT WITH END SECTIONS
	RAILROAD CROSS BUCK		PROPOSED CULVERT WITH END SECTIONS
	RAILROAD GATE ARM		BUILDING OUTLINE
	RAILROAD TRACKS		FENCE LINE
	LIGHT POLE		SAW CUT REQ'D
	WOOD POLE		SILT FENCE
	TRAFFIC SIGNAL		GUARD RAIL
	TRAFFIC SIGNAL MAST ARM		DITCH CHECK
	CONIFEROUS TREE		INLET PROTECTION
	DECIDUOUS TREE		TRACKING PAD
	TREE OR BRUSH LINE		TURBIDITY BARRIER OR SHEET PILING
	BED ROCK (IN PROFILE VIEW)		SANDBAG COFFERDAM
	HANDICAPPED PARKING STALL		SLOPE INTERCEPT
	EXISTING SPOT ELEVATION		LIMITS OF DISTURBANCE
	PROPOSED SPOT ELEVATION		ASPHALT PAVEMENT
	DRAINAGE HIGH POINT		CONCRETE SIDEWALK/DRIVEWAY
	DRAINAGE DIRECTION		GRAVEL
	EXISTING MANHOLE		RIP-RAP (SIZE AS SPECIFIED)
	PROPOSED MANHOLE		PROPOSED TURF REINFORCEMENT MAT (TRM)
	EXISTING INLET		EXISTING DELINEATED WETLANDS
	PROPOSED INLET		
	EXISTING YARD DRAIN		
	PROPOSED YARD DRAIN		
	EXISTING CLEAN OUT		
	PROPOSED CLEAN OUT		
	EXISTING DOWNSPOUT		
	PROPOSED DOWNSPOUT		
	EXISTING WATER VALVE		
	PROPOSED WATER VALVE		
	EXISTING CURB STOP		
	PROPOSED CURB STOP		
	EXISTING FIRE HYDRANT		
	PROPOSED FIRE HYDRANT		
	PROPOSED WATER FITTING		
	PROPOSED WATER REDUCER		
	PROPOSED ENDCAP		
	GAS VALVE		

EROSION & SEDIMENT CONTROL PLAN

BEST MANAGEMENT PRACTICES:

THE CONTRACTOR IS RESPONSIBLE FOR FURNISHING, INSTALLING, MAINTAINING AND REMOVING BEST MANAGEMENT PRACTICES IN ACCORDANCE WITH WISCONSIN DEPARTMENT OF NATURAL RESOURCES (DNR) TECHNICAL STANDARDS. THESE STANDARDS MAY BE FOUND ON THE DNR WEBSITE AT <http://www.dnr.wi.gov/runoff/stormwater/techsids.htm>. THE MINIMUM BEST MANAGEMENT PRACTICES SPECIFIED FOR THIS PROJECT ARE AS FOLLOWS:

[] LAND APPLICATION OF ADDITIVES (1050)	[X] DE-WATERING (1061)
[] WATER APPLICATION OF ADDITIVES (1051)	[X] DITCH CHECK (1062)
[] NON-CHANNEL EROSION MAT (1052)	[] SEDIMENT TRAP (1063)
[] CHANNEL EROSION MAT (1053)	[] SEDIMENT BASIN (1064)
[] VEGETATIVE BUFFER (1054)	[X] RIP-RAP (1065)
[] SEDIMENT BALE BARRIER (1055)	[] CONSTRUCTION DIVERSION (1066)
[X] PERIMETER SEDIMENT CONTROL (1056)	[X] TEMPORARY GRADING PRACTICES (1067)
[X] TRACKOUT CONTROL (1057)	[X] DUST CONTROL (1068)
[X] MULCHING (1058)	[] TURBIDITY BARRIER (1069)
[X] SEEDING (1059)	[] SILT CURTAIN (1070)
[X] STORM DRAIN INLET PROTECTION (1060)	[] HORIZONTAL DIRECTIONAL DRILLING (1072)

THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES AND IMPLEMENT BEST MANAGEMENT PRACTICES TO PREVENT OR REDUCE ALL OF THE FOLLOWING:

- DEPOSITION OR TRACKING OF SOIL ONTO STREETS BY VEHICLES.
- DISCHARGE OF SEDIMENT INTO STORM WATER INLETS.
- DISCHARGE OF SEDIMENT INTO ADJACENT STREAMS, RIVERS, LAKES AND WETLANDS.
- DISCHARGE OF SEDIMENT FROM DITCHES AND STORM SEWERS THAT FLOW OFFSITE.
- DISCHARGE OF SEDIMENT FROM DEWATERING ACTIVITIES.
- DISCHARGE OF SEDIMENT FROM SOIL STOCKPILES EXISTING FOR 7 DAYS OR MORE.
- DISCHARGE OF SEDIMENT FROM EROSION OUTLET FLOWS.
- TRANSPORT OF CHEMICALS, CEMENT AND BUILDING MATERIALS BY RUNOFF.
- TRANSPORT OF UNTREATED VEHICLE AND WHEEL WASH WATER BY RUNOFF.

THE CONTRACTOR SHALL IMPLEMENT THE FOLLOWING PREVENTATIVE MEASURES:

- PRESERVE EXISTING VEGETATION WHENEVER POSSIBLE.
- MINIMIZE SOIL COMPACTION AND PRESERVE TOPSOIL.
- MINIMIZE LAND DISTURBANCES ON SLOPES OF 20% OR MORE.
- MINIMIZE THE AMOUNT OF SOIL EXPOSED AT ANY ONE TIME.
- DIVERT CLEAR WATER AWAY FROM EXPOSED SOILS.
- TEMPORARILY STABILIZE EXPOSED SOILS THAT WILL NOT BE ACTIVE FOR 14 DAYS OR MORE. USE MULCHING, SEEDING, POLYACRYLAMIDE OR GRAVELING TO STABILIZE.
- PERMANENTLY STABILIZE EXPOSED SOILS AS SOON AS POSSIBLE.
- CONTRACTOR SHALL EDUCATE ITS EMPLOYEES AND SUBCONTRACTORS ABOUT PROPER SPILL PREVENTION AND RESPONSE PROCEDURES. IF A SPILL OCCURS, THE CONTRACTOR SHALL EVACUATE THE AREA AND IMMEDIATELY NOTIFY THE LOCAL MUNICIPALITY, FIRE DEPARTMENT OR 911 EMERGENCY SYSTEM. IF NO FIRE, EXPLOSION OR LIFE / HEALTH SAFETY HAZARD EXISTS, THE NEXT STEP IS TO CONTAIN THE SPILL AND PERFORM CLEANUP. USE DRY CLEANUP METHODS, NOT WET.

THE CONTRACTOR IS RESPONSIBLE FOR REPAIRING OR REPLACING BEST MANAGEMENT PRACTICES DESTROYED AS A RESULT OF CONSTRUCTION ACTIVITIES BY THE END OF THE WORK DAY. THE CONTRACTOR IS RESPONSIBLE FOR REPLACING BEST MANAGEMENT PRACTICES TEMPORARILY REMOVED FOR CONSTRUCTION ACTIVITY AS SOON AS THOSE ACTIVITIES ARE COMPLETED. THE CONTRACTOR IS RESPONSIBLE FOR REMOVING AND DISPOSING OF TEMPORARY BEST MANAGEMENT PRACTICES AFTER CONSTRUCTION IS COMPLETE AND PERMANENT VEGETATION IS ESTABLISHED.

INSPECTION & MAINTENANCE:

THE CONTRACTOR IS RESPONSIBLE FOR INSPECTING BEST MANAGEMENT PRACTICES WEEKLY, AND WITHIN 24 HOURS FOLLOWING A RAINFALL OF 0.5 INCHES OR GREATER. WRITTEN DOCUMENTATION OF EACH INSPECTION SHALL BE KEPT AT THE CONSTRUCTION SITE AND SHALL INCLUDE THE FOLLOWING INFORMATION: DATE, TIME, AND LOCATION OF INSPECTION; NAME OF INDIVIDUAL WHO PERFORMED THE INSPECTION; AN ASSESSMENT OF THE CONDITION OF BEST MANAGEMENT PRACTICES; A DESCRIPTION OF ANY BEST MANAGEMENT PRACTICE IMPLEMENTATION AND MAINTENANCE PERFORMED; AND A DESCRIPTION OF THE PRESENT PHASE OF CONSTRUCTION. THE CONTRACTOR IS RESPONSIBLE FOR MAINTAINING, REPAIRING, OR REPLACING BEST MANAGEMENT PRACTICES AS NECESSARY WITHIN 24 HOURS OF AN INSPECTION OR NOTIFICATION. THE CONTRACTOR IS RESPONSIBLE FOR INSPECTING, MAINTAINING, REPAIRING, OR REPLACING BEST MANAGEMENT PRACTICES UNTIL ALL LAND DISTURBING CONSTRUCTION ACTIVITY IS COMPLETED AND A UNIFORM PERENNIAL VEGETATIVE COVER IS ESTABLISHED WITH A DENSITY OF AT LEAST 70%.

THE CONTRACTOR IS RESPONSIBLE FOR POSTING THE PERMIT IN A CONSPICUOUS LOCATION ON THE CONSTRUCTION SITE. THE CONTRACTOR IS RESPONSIBLE FOR KEEPING A COPY OF THE APPROVED REPORTS, PLANS, AMENDMENTS, INSPECTION REPORTS, AND PERMITS AT THE CONSTRUCTION SITE AT ALL TIMES UNTIL ALL LAND DISTURBING CONSTRUCTION ACTIVITY IS COMPLETED AND A UNIFORM PERENNIAL VEGETATIVE COVER IS ESTABLISHED WITH A DENSITY OF AT LEAST 70%. THE CONTRACTOR IS RESPONSIBLE FOR NOTIFYING THE OWNER WHEN THE VEGETATIVE DENSITY REACHES AT LEAST 70%. THE OWNER IS RESPONSIBLE FOR TERMINATING DNR PERMIT COVERAGE.

AMENDMENTS:

THE CONTRACTOR IS RESPONSIBLE FOR AMENDING THE EROSION & SEDIMENT CONTROL PLAN IF: THERE IS A CHANGE IN CONSTRUCTION, OPERATION OR MAINTENANCE AT THE SITE WHICH HAS THE REASONABLE POTENTIAL FOR THE DISCHARGE OF POLLUTANTS; THE ACTIONS REQUIRED BY THE PLAN FAIL TO REDUCE THE IMPACTS OF POLLUTANTS CARRIED BY CONSTRUCTION SITE RUNOFF; OR IF THE DNR NOTIFIES THE APPLICANT OF CHANGES NEEDED IN THE PLAN. THE DNR AND OWNER SHALL BE NOTIFIED 5 WORKING DAYS PRIOR TO MAKING CHANGES TO THE PLAN.

Item 2.a.

McMAHON
ENGINEER-ARCHITECT

McMAHON ASSOCIATES, INC.
1445 McMAHON DRIVE NEENAH, WI 54956
Mailing: P.O. BOX 1025 NEENAH, WI 54957-1025
PH 920/751-4200 FX 920/751-4284 MCMGRP.C

DESIGNED	DRAWN
AWS	AWS
PROJECT NO.	K0006-092200453
DATE	NOV., 2022
SHEET NO.	01

COMPANY WOODS POND
CITY OF KAUKAUNA, OUTAGAMIE CO., WI
ABBREVIATIONS SYMBOLS & NOTES

DESIGNED	DRAWN
AWS	AWS
PROJECT NO.	K0006-092200453
DATE	NOV., 2022
SHEET NO.	01

g:\schmidt, W.\PROJECTS\K0006\092200453\CADD\Civil3D\Plan Streets\02 Survey Control.dwg, 02 survey control, Plot Date: 7/20/2023 11:18 AM, xrefs: (x-is prop lines company woods, x-aerial county 2020)




NOTE:
PRIOR TO CONSTRUCTION, THE CONTRACTOR SHALL VERIFY PROPOSED SITE GRADES BY FIELD CHECKING TWO (2) BENCHMARKS AND A MINIMUM OF ONE (1) SITE FEATURE AS SHOWN ON THESE PLANS. THE CONTRACTOR SHALL ALSO VERIFY HORIZONTAL CONTROL BY FIELD CHECKING SEVERAL CONTROL POINTS AND SHALL IMMEDIATELY NOTIFY MCMAHON OF ANY DISCREPANCIES.

VERTICAL DATUM
ELEVATIONS ARE REFERENCED TO NGS DATA:
CONTROL POINT NAME: BUCHANAN C GPS
POINT ID: DF5990 NAVD 88 DATUM
BY GPS OBSERVATION TO ELEVATION = 728.28 (2007 ADJUSTMENT)
PER FIELD BOOK 1520 PAGE 55

HORIZONTAL DATUM:
COORDINATES ARE REFERENCED TO THE WISCONSIN COUNTY COORDINATE SYSTEM AS PUBLISHED FOR OUTAGAMIE COUNTY NAD 83 (1991)

Preliminary - Not for Construction



HORIZONTAL CONTROL POINTS			
POINT #	NORTHING	EASTING	DESCRIPTION
4	563809.82	866481.14	MAG NAIL
5	563601.09	866538.94	MAG NAIL

VERTICAL BENCHMARK CONTROL		
POINT #	ELEVATION	DESCRIPTION
6	711.03	HYDRANT ARROW
7	713.60	HYDRANT ARROW

DESIGNED AWS	DRAWN AWS
PROJECT NO. K0006-092200453	
DATE NOV., 2022	
SHEET NO.	

02

5

COMPANY WOODS POND
CITY OF KAUKAUNA, OUTAGAMIE CO., WI
SURVEY CONTROL

McMahon Associates, Inc. provides this drawing & data, regardless of the medium, for the sole use of the client. All rights, including copyright, are reserved by McMahon Associates, Inc. The client, and/or recipient agrees to hold McMahon Associates, Inc. harmless for any reuse of or changes made to this drawing without the written consent by McMahon Associates, Inc.


McMAHON
ENGINEERING ARCHITECT
McMAHON ASSOCIATES, INC.
1445 McMAHON DRIVE NEENAH, WI 54956
Mailing: P.O. BOX 1025 NEENAH, WI 54957-1025
PH 920.751.4200 FX 920.751.4284 MCMGRP.C

REVISION


DATE

NO.

Item 2.a.



aschmidt, W:\PROJECTS\K0006\092200453\CADD\Civil3D\Plan Sheets\04 PROPOSED POND PLAN.dwg, 04 proposed pond plan, Plot Date: 7/20/2023 11:18 AM, xrefs: (x--exist topo company woods pond, x--all points company woods pond, x--exist shade company woods pond, x--proposed company woods)



Preliminary - Not for Construction

POND 2-YEAR WATER SURFACE ELEVATION = 697.55

COMPANY WOODS POND
CITY OF KAUKAUNA, OUTAGAMIE CO., WI
PROPOSED POND PLAN


DESIGNED AWS	DRAWN AWS
PROJECT NO. K0006-092200453	
DATE NOV., 2022	
SHEET NO.	

04

McMAHON ASSOCIATES, INC. provides this drawing & data, regardless of the medium, for the use of the client and/or recipient. The client and/or recipient agrees to hold the information contained herein in confidence and to indemnify and hold harmless for any reuse of or changes made to the original information without the written consent by McMahon Associates, Inc.


McMAHON ASSOCIATES, INC.
1445 McMAHON DRIVE NEENAH, WI 54956
Mailing: P.O. BOX 1025 NEENAH, WI 54957-1025
PH 920.751.4200 FX 920.751.4284 MCMGRP.C

Item 2.a.




Preliminary - Not for Construction

gschmidt, W:\PROJECTS\K0006\092200453\CADD\Civil3D\Plan Sheets\00 Title-Notes-Details.dwg, 06 miscellaneous detail, Plot Date: 7/20/2023 11:18 AM, xref:none




TOP TRASH RACK DETAIL PLAN VIEW



ALL STRUCTURAL STEEL SHALL BE GALVANIZED AND PAINTED FOLLOWING GALVANIZING (SEE DETAIL).

ELEMENT KEY

- 1 HSS 3x3x1/4
- 2 1/4"x3" PLATE @ 3"o.c. MAXIMUM
- 3 1/2" DIA BAR @ 10"o.c. MAXIMUM
- 4 HSS2x2x1/4
- 5 1/4"x2" HORIZONTAL PLATE WELDED TO SIDE OF HSS3x3x1/4
- 6 1/4"x2" PLATE @ 2"o.c. MAXIMUM
- 7 3/8" DIA. SST BOLT
- 8 3/8" DIA. SST ADHESIVE ANCHOR @ 24"o.c. MAXIMUM
- 9 3/8"x5" CONT. PLATE




STRUCTURAL STEEL


1. STRUCTURAL STEEL SHALL MEET THE FOLLOWING SPECIFICATIONS:
BARS & PLATES - ASTM A36
ANCHOR BOLTS - ASTM A36
WELDS - E70 XX
ALL STEEL SHALL BE GALVANIZED, AND PAINTED ONCE FABRICATED.
2. ALL DETAILING, FABRICATION AND ERECTION SHALL CONFORM TO THE AISC "LOAD AND RESISTANCE FACTOR DESIGN SPECIFICATIONS FOR STRUCTURAL STEEL BUILDINGS" AND "CODE OF STANDARD PRACTICE FOR BUILDINGS AND BRIDGES", CURRENT EDITION.
3. ALL WELDING SHALL BE PERFORMED BY A CERTIFIED WELDER IN ACCORDANCE WITH A.W.S. CODE FOR WELDING IN BUILDING CONSTRUCTION. SURFACES FOR FIELD WELDED MATERIAL SHALL BE PROPERLY PREPARED PRIOR TO BEING WELDED TO ASSURE A GOOD QUALITY WELD. REMOVE PAINT, GREASE, DIRT, ETC.
4. ALL STEEL MEMBERS SHALL BE WELDED WITH A 3/16" CONTINUOUS FILLET WELD (UNLESS OTHERWISE NOTED)
5. ALL WELDS SHALL BE TOUCHED UP WITH GALVANIZING COMPOUND, THEN PAINTED ACCORDING TO:

PAINT:

SURFACE	TNEMEC COATING SYSTEM	COVERAGE SQ. FT./GAL	THICKNESS /COAT DMT	COLOR
STEEL (OUTDOORS)	SHOP PRIMER 69-1255 BEIGE	277	4.0	BEIGE
	1 COAT 69 H.B. EPOXY	221	5.0	BLACK
	1 COAT 74 ENDURA-SHELD IV	310	3.0	BLACK



SECTION A-A




NOTES:


1. WHEN FRAME HEIGHT IS 24 INCHES OR LESS, PROVIDE (1) ANCHOR PER VERTICAL LEG, OTHERWISE PROVIDE TWO OR MORE ANCHOR @ 24" O.C. MAX.
2. WHEN FRAME LENGTH IS 12" OR LESS, PROVIDE (1) ANCHOR PER HORIZONTAL LEG, OTHERWISE PROVIDE TWO OR MORE ANCHORS @ 24" O.C. MAX.
3. PROVIDE 3/8" EPOXY ANCHOR EMBEDDED 4" MIN. INTO CONCRETE WHERE REQUIRED BY THIS DRAWING OR NOTES.
4. SEE OUTLET STRUCTURE DETAIL FOR TRASH RACK FRAME SIZE.

FRONT TRASH RACK DETAIL-ELEVATION VIEW


ALL STRUCTURAL STEEL SHALL BE GALVANIZED AND PAINTED FOLLOWING GALVANIZING (SEE DETAIL).



PLAN VIEW



FRONT VIEW SECTION A-A



SIDE VIEW SECTION B-B

POND OUTLET STRUCTURE

CLAY LINER SPECIFICATIONS (TYP.)

LINER THICKNESS = 4 FEET
IN PLACE HYDRAULIC CONDUCTIVITY = 1 X 10⁻⁷ CM/SEC OR LESS
MINIMUM OF 50% BY WEIGHT WHICH PASSES THE 200 SIEVE
AVERAGE LIQUID LIMIT OF 25 OR GREATER, NONE LESS THAN 20
AVERAGE PLASTICITY INDEX OF 12 OR GREATER, NONE LESS THAN 10


ALL CLAY LAYERS IN THE LINER TO BE CONSTRUCTED IN LIFT HEIGHTS NO GREATER THAN 6 INCHES AFTER COMPACTION USING FOOTED COMPACTION EQUIPMENT HAVING FEET AT LEAST AS LONG AS THE LOOSE LIFT HEIGHT. CLAY IS TO BE DISKED OR OTHERWISE MECHANICALLY PROCESSED BEFORE COMPACTION TO BREAK UP CLODS AND ALLOW FOR MOISTURE ADJUSTMENT. CLOD SIZE TO BE NO GREATER THAN 4 INCHES.

A SUFFICIENT NUMBER OF PASSES OF THE COMPACTION EQUIPMENT IS TO BE MADE OVER EACH LIFT OF CLAY TO ENSURE COMPLETE REMOLDING OF THE CLAY.

ALL CLAY TO BE COMPACTED TO 90% MODIFIED OR 95% STANDARD PROCTOR DENSITY AT A MOISTURE CONTENT OF AT LEAST 2% WET OF OPTIMUM IF USING THE MODIFIED PROCTOR METHOD AND WET OF OPTIMUM IF USING THE STANDARD PROCTOR METHOD, BASED ON THE CHARACTERISTICS OF THE APPROPRIATE PROCTOR CURVE FOR THE CLAY BEING PLACED. THE CLAY LINER IS TO BE KEYED TOGETHER TO FORM A CONTINUOUS CLAY SEAL, SEE DETAIL.


CLAY LINER SHALL BE PLACED OVER NATIVE SOILS THAT DO NOT SATISFY THE CLAY LINER SPECIFICATIONS. A GEOTECHNICAL ENGINEER SHALL DETERMINE WHICH SOILS DO NOT SATISFY THE CLAY LINER SPECIFICATIONS. THE GEOTECHNICAL ENGINEER SHALL INSPECT SOILS WITHIN THE PERMANENT POOL AND UP TO THE POND'S 2-YEAR, 24-HOUR WATER SURFACE ELEVATION. UPON COMPLETION OF THE LINER, A GEOTECHNICAL ENGINEER REGISTERED IN WISCONSIN SHALL PROVIDE A LETTER OF OPINION INDICATING IF THE CLAY LINER SATISFIES THESE SPECIFICATIONS.

WHERE STORM SEWER, CULVERT OF OTHER STRUCTURE PASSES THROUGH NATIVE CLAY OR CLAY LINER, THE CONTRACTOR SHALL INSTALL CLAY LINER, BENTONITE OR CONCRETE SLURRY (2.0 BAG/C.Y. MIX) BEDDING IN LIEU OF GRAVEL BEDDING & BACKFILL. THE LINER & BENTONITE OR SLURRY SHALL MINIMIZE SEEPAGE ALONG THE OUTSIDE WALL OF THE STORM SEWER, CULVERT OR STRUCTURE INCLUDING AT THE PIPE JOINT THE HOLES AND PIPE JOINTS. IF BENTONITE IS USED, THE BENTONITE SHALL BE POSITIONED BETWEEN PIPE JOINTS. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ADEQUATE BEDDING SUPPORT FOR THE STORM SEWER, CULVERT OR STRUCTURE.




CLAY LINER DETAIL

gschmidt, W:\PROJECTS\K0006\092200453\CADD\Civil3D\Plan Sheets\00 Title-Notes-Details.dwg, 07 miscellaneous detail, Plot Date: 7/20/2023 11:18 AM, xrefs:none





RIP-RAP

1. RIP-RAP SHALL BE IN ACCORDANCE WITH SECTION 606, WIS-DOT STANDARD SPECIFICATIONS FOR HIGHWAY AND STRUCTURE CONSTRUCTION, CURRENT EDITION.
2. RIP-RAP SHALL BE ANGULAR, ROUND RIP-RAP IS NOT PERMITTED.



RIPRAP AT STORM SEWER OUTFALL




* MANUFACTURED TRACKOUT CONTROL DEVICE PER WDMR TECHNICAL STANDARD 1057 MAY BE USED.

GENERAL NOTES

MANUFACTURED ALTERNATIVES APPROVED AND LISTED ON THE DEPARTMENT'S EROSION CONTROL PRODUCT ACCEPTABILITY LIST MAY BE SUBSTITUTED.

WHEN REMOVING OR MAINTAINING INLET PROTECTION, CARE SHALL BE TAKEN SO THAT THE SEDIMENT TRAPPED ON THE GEOTEXTILE FABRIC DOES NOT FALL INTO THE INLET. ANY MATERIAL FALLING INTO THE INLET SHALL BE REMOVED IMMEDIATELY.

- ① FINISHED SIZE, INCLUDING FLAP POCKETS WHERE REQUIRED, SHALL EXTEND A MINIMUM OF 10" AROUND THE PERIMETER TO FACILITATE MAINTENANCE OR REMOVAL.
- ② FOR INLET PROTECTION, TYPE C (WITH CURB BOX), AN ADDITIONAL 18" OF FABRIC IS WRAPPED AROUND THE WOOD AND SECURED WITH STAPLES. THE WOOD SHALL NOT BLOCK THE ENTIRE HEIGHT OF THE CURB BOX OPENING.
- ③ FLAP POCKETS SHALL BE LARGE ENOUGH TO ACCEPT WOOD 2X4.



INLET PROTECTION, TYPE C (WITH CURB BOX)

INSTALLATION NOTES


TYPE C

TRIM EXCESS FABRIC IN THE FLOW LINE TO WITHIN 3" OF THE GRATE. THE CONTRACTOR SHALL DEMONSTRATE A METHOD OF MAINTENANCE, USING A SEWN FLAP, HAND HOLDS OR OTHER METHOD TO PREVENT ACCUMULATED SEDIMENT FROM ENTERING THE INLET.


TYPE D

DO NOT INSTALL INLET PROTECTION TYPE D IN INLETS SHALLOWER THAN 30", MEASURED FROM THE BOTTOM OF THE INLET TO THE TOP OF THE GRATE. TRIM EXCESS FABRIC IN THE FLOW LINE TO WITHIN 3" OF THE GRATE. THE INSTALLED BAG SHALL HAVE A MINIMUM SIDE CLEARANCE, BETWEEN THE INLET WALLS AND THE BAG, MEASURED AT THE BOTTOM OF THE OVERFLOW HOLES, OF 3". WHERE NECESSARY THE CONTRACTOR SHALL CINCH THE BAG, USING PLASTIC ZIP TIES, TO ACHIEVE THE 3" CLEARANCE. THE TIES SHALL BE PLACED AT A MAXIMUM OF 4" FROM THE BOTTOM OF THE BAG.

STORM DRAIN INLET PROTECTION



Preliminary - Not for Construction



INLET PROTECTION, TYPE D

(CAN BE INSTALLED IN ANY INLET TYPE WITH OR WITHOUT A CURB BOX AS PER NOTE ②)

Item 2.a.

McMAHON

ENGINEER-ARCHITECT

McMAHON ASSOCIATES, INC.
1445 McMAHON DRIVE NEENAH, WI 54956
Mailing: P.O. BOX 1025 NEENAH, WI 54957-1025
PH 920/751-4200 FX 920/751-4284 MCMGRP.C

McMahon Associates, Inc. provides the drawing & design, regardless of the project size, for the design & construction of the project. All rights, including design, are reserved. The client and/or recipient agrees to hold McMahon Associates, Inc. harmless for any reuse of or changes made to the drawing without the written consent by McMahon Associates, Inc.

DESIGNED
AWS

DRAWN
AWS

PROJECT NO.
K0006-092200453

DATE
NOV., 2022

SHEET NO.
07

COMPANY WOODS POND
CITY OF KAUKAUNA, OUTAGAMIE CO., WI
MISCELLANEOUS DETAIL

10